



ハーフカップリング、およびボス (差込み: SW)

炭素鋼



Sch80

※炭素鋼							mm
A呼称	B呼称	B	F	C	D	O	L
8A	1/4	14.3	22.0	10.0	7.8	15.9	25.9
10A	3/8	17.8	27.0	13.0	10.9	17.5	30.5
15A	1/2	22.2	32.0	13.0	14.3	22.2	35.2
20A	3/4	27.7	38.0	15.0	19.4	23.8	38.8
25A	1	34.5	46.0	16.0	25.0	28.6	44.6
32A	1・1/4	43.2	57.0	18.0	32.9	30.2	48.2
40A	1・1/2	49.1	63.0	19.0	38.4	31.8	50.8
50A	2	61.1	75.0	22.0	49.5	41.3	63.3
65A	2・1/2	77.1	95.0	26.0	62.3	42.9	68.9
80A	3	90.0	110.0	29.0	73.9	44.5	73.5
100A	4	115.4	138.0	35.0	97.1	47.5	82.5

Sch160

※炭素鋼							mm
A呼称	B呼称	B	F	C	D	O	L
15A	1/2	22.2	36.0	14.0	12.3	22.2	36.2
20A	3/4	27.7	42.0	16.0	16.2	23.8	39.8
25A	1	34.5	50.0	18.0	21.2	28.6	46.6
32A	1・1/4	43.2	60.0	19.0	29.9	30.2	49.2
40A	1・1/2	49.1	70.0	22.0	34.4	31.8	53.8
50A	2	61.1	85.0	25.0	43.1	41.3	66.3
65A	2・1/2	77.1	105.0	28.0	57.3	42.9	70.9
80A	3	90.0	120.0	31.0	66.9	44.5	75.5